

# GPS-NEMA4-OE™

## NEMA 4X Control Panel

### Product Description

The GPS-NEMA4-OE is a NEMA 4X rated fiberglass enclosure designed to house one GPS-iMOD® power supply. The panel adds a superior finished look to any project while providing the required protection against foreign substances such as water and dust when the power supplies are mounted in non-NEMA 1 rated environment.

### Standard Features

Illuminated On/Off Switch, Power On, System Off and Plasma On LED Indicators.

### Benefits

Provides protection for the GPS-iMOD power supply when installation is required in wet or outdoor locations. The panel indicates system performance.




### Specifications

Input Voltage (AC Only*)	24V/120V/208-240V	Power Entry	1/4" Heyco Liquid-Tight Connector
GPS-iMOD Amps	0.63A @ 24V, 0.13A @ 120V, 0.07A @ 208-240V	Compliance	OSHPD Seismic (OSP)
Power	15 Watts for GPS-iMOD	Weight	13.99 lbs with power supply 9.36 lbs without power supply
Frequency	50/60Hz		
Output Voltage	5.0kV RMS for GPS-iMOD		
Output Current	3 mA for GPS-iMOD		

\*GPS-iMOD can accept 24V to 240V

### Commercial Applications

- Indoor or Outdoor
- Required only when the GPS-iMOD power supply is in wet, dirty or otherwise non-NEMA 1 rated environments.



Engineering Air for a Cleaner World™

Global Plasma Solutions, Inc.  
[www.GlobalPlasmaSolutions.com](http://www.GlobalPlasmaSolutions.com)